# EB 🗲 **BAKING OVEN**

#### • STAINLESS STEEL STRUCTURE

High quality stainless steel covers all body.

#### • EXCELLENT HEATING EFFICIENCY

Electric type equipped with high quality heating element

#### • INDEPENDENT CONTROL

Each layer work separately, top and bottom temperature can be controlled separately or work independently.

#### • BUILT-IN LIGHT

Stainless Steel door with built-in light.

#### ANTI-HOT HANDLE

Anti-hot handle can insulation against hot. avoid burns bakers' hand.

#### • MECHANICAL CONTROL WITH TIMER

Qualify mechanical control panel. The temperature of electric oven range 0-400"C with micro-computer display.

#### • OEM & ODM DESIGN WITH YOUR REQUEST

Customization machine dimension. Optional: Digital control/steam/stone plate.











**EB-24** 

**EB-12** 

MODEL	EB-11	EB-22	EB-33	EB-12	EB-24	EB-36	EB-39
<b>5</b> VOLTAGE(V)	220~	220/380~	220/380~	220/380~	220/380~	380~	380~
POWER(kW)	3	6	9	7	14	21	27
<b>⚠</b> TEMPERATURE(°C)	300	300	300	300	300	300	300
□ DECK/TRAY	1/1	2/2	3/3	1/2	2/4	3/6	3/9
TRAY SIZE(mm)	400*600	400*600	400*600	400*600	400*600	400*600	400*600
DIMENSION(mm)	922*630*410	922*630*755	922*630*1080	1210*805*540	1210*805*1130	1210*805*1335	1645*805*1395



# • STAINLESS STEEL STRUCTURE

High quality stainless steel covers all body.

#### • EXCELLENT HEATING EFFICIENCY

Gas type equipped with stainless steel gas burner

#### • INDEPENDENT CONTROL

Each layer work separately, top and bottom temperature can be controlled separately or work independently.

#### BUILT-IN LIGHT

Stainless Steel door with built-in light.

#### ANTI-HOT HANDLE

Anti-hot handle can insulation against hot, avoid burns bakers' hand.

## • MECHANICAL CONTROL WITH TIMER

Qualify mechanical control panel. The temperature of electric oven range 0-400"C with micro-computer display.

### • OEM & ODM DESIGN WITH YOUR REQUEST

Customization machine dimension. Optional: Digital control/steam/stone plate.



**GB-36** 







**GB-12** 

**GB-24** 

MODEL	GB-11	GB-22	GB-33	GB-12	GB-24	GB-36	GB-39
<b>F</b> VOLTAGE(V)	220~	220~	220~	220~	220~	220~	220~
POWER(kW)	0.08	0.16	0.24	0.1	0.2	0.3	0.36
THERMAL POWER (	(MJ/H) 16	32	48	25	50	75	120
	300	300	300	300	300	300	300
□ DECK/TRAY	1/1	2/2	3/3	1/2	2/4	3/6	3/9
TRAY SIZE(mm)	400*600	400*600	400*600	400*600	400*600	400*600	400*600
DIMENSION(mm)	1030*650*525	1030*650*1015	1030*650*1500	1310*825*610	1310*825*1220	1310*825*1700	1310*825*1690