CONVECTION OVEN





CONVECTION

Hot air circulation 360 degrees evenly heated, baking color more bright.

• PRECISE TEMPERATURE CONTROL

High precision electronic probe is used to detect the temperature of the oven in real time and display the temperature in real time, which is more accurate and stable than the mechanical oven

INSULATION COTTON

High quality insulation cotton makes the inner chamber insulation effect better and improves the baking quality.

MEMORY MENU

12 memory menus can be set up, convenient and quick, one key start.

EXPLOSION PROOF LAMP

Built in high temperature explosion-proof bulb, can observe the whole baking state.

CLEAR WINDOW

Visual toughened glass can control the fermentation condition inside the box in real time, which is easy to adjust at any time.



ERF-5D



ERF-10D

OPTIONAL Control panel







MODEL	ERF-5D	ERF-10D	ERF-20D	ERF-5Q	ERF-10Q	ERF-20Q
F VOLTAGE(V)	380	380	380	220	220	220
POWER(KW)	7.5	15	30	0.6	1.2	2
TRAYS	5	10	20	5	10	20
TRAY SIZE(mm)	400*600	400*600	400*600	400*600	400*600	400*600
	300	300	300	300	300	300
N.W.(KG)	135	195	450	155	255	450
DIMENSION(mm)	800*1120*1540	800*1120*1780	1500*1120*1740	800*1150*1540	800*1220*1780	1680*1310*1740

ROTARY CONVECTION OVEN (?)





CONVECTION

Hot air circulation 360 degrees evenly heated, baking color more bright.

• PRECISE TEMPERATURE CONTROL

High precision electronic probe is used to detect the temperature of the oven in real time and display the temperature in real time, which is more accurate and stable than the mechanical oven

INSULATION COTTON

High quality insulation cotton makes the inner chamber insulation effect better and improves the baking quality.

MEMORY MENU

12 memory menus can be set up, convenient and quick, one key start.

• EXPLOSION PROOF LAMP

Built in high temperature explosion-proof bulb, can observe the whole baking state.

CLEAR WINDOW

Visual toughened glass can control the fermentation condition inside the box in real time, which is easy to adjust at any time.



ERF-5D



ERF-10D

OPTIONAL Control panel





MODEL	ERF-5D	ERF-10D	ERF-5Q	ERF-10Q
§ VOLTAGE(V)	380	380	220	220
POWER(KW)	7.5	15	0.6	1.2
TRAYS	5	10	5	10
TRAY SIZE(mm)	400*600	400*600	400*600	400*600
 ■ TEMPERATURE(°C)	300	300	300	300
N.W.(KG)	135	195	155	255
DIMENSION(mm)	800*1120*1540	800*1120*1780	800*1150*1540	800*1220*1780